

IDNDR PROGRAMME FORUM 1999



"Partnerships for a Safer World  
in the 21st Century"



**IDNDR**  
**1990 - 2000**

Building a Culture of Prevention

**VAW**

Laboratory of Hydraulics,  
Hydrology and Glaciology  
of the Swiss Federal Institute  
of Technology, Zurich

Coping study on

# **DISASTER RESILIENT INFRASTRUCTURE**

Commissioned by the  
Secretariat for the International Decade for  
Natural Disaster Reduction  
for the  
IDNDR Programme Forum 1999  
"Partnerships for a safer world in the 21st century"



**UNITED NATIONS**  
New York and Geneva, 1999

## PREFACE

In December 1998 an agreement was signed to provide support for the organization of IDNDR Program Forum to be held in July 1999 and its preparatory process through undertaking a coping study on the theme *Disaster Resilient Infrastructure* by Versuchsanstalt für Wasserbau, Hydrologie und Glaziologie (VAW) of ETH Zurich within the project "Coping Studies on Research Needs for Future Disaster Reduction". These coping studies are implemented and coordinated by the Graduate Institute of International Studies, Geneva, the Programme for the Study of International Organizations (HEI-PSIO).

VAW is doing research only in some fields of natural hazards i.e. floods, debris flow, impulse waves and ice avalanches. Therefore, it was necessary to find partners to contribute to this report. Fortunately it was possible to find experts in each field of natural hazard that were willing to write a chapter of this report. I take this opportunity to thank all authors for their valuable contributions. A detailed list of all authors is provided.

To contribute to the coping study was a challenge. It is not easy to summarize the essentials on such limited space. And if the report gets too voluminous it would be too difficult to read. I hope that the right equilibrium was found and this report introduces the reader on the main problems, risks, but also research needs and necessary activities to be taken in relation to natural hazards.

I want to thank Dr. Warner, Director of PSIO, the project coordinator for the excellent cooperation and Dr. Hager for having coordinated as a project head.

Prof. Dr. H.-E. Minor

## Contributing Authors

Ammann, Walter J.	Dr., Head, Swiss Federal Institute for Snow and Avalanche Research (SLF), Flüelastrasse 11, 7260 Davos Dorf
Böll, Albert	WSL, Abtl. Wasser-, Erd- und Felsbewegungen, 8903 Birmensdorf
Bonnard, Christophe	Soil Mechanics Laboratory, Swiss Federal Institute of Technology (EPFL), 1015 Lausanne
Conedera, Marco	FNP Sottostazione Sud delle Alpi, Via Belsoggiorno 22, 6504 Bellinzona
Descoeudres, François	Prof. Dr., Rock Mechanics Laboratory, Swiss Federal Institute of Technology (EPFL), 1015 Lausanne
Föhn, Paul M.B.	Dr., Swiss Federal Institute for Snow and Avalanche Research (SLF), Flüelastrasse 11, 7260 Davos Dorf
Funk, Martin	Dr., Laboratory for Hydraulics, Hydrology and Glaciology (VAW), Swiss Federal Institute of Technology (ETH), 8092 Zürich
Gerber, Werner	WSL, Abtl. Wasser-, Erd- und Felsbewegungen, 8903 Birmensdorf
Hager, Willi H.	Prof. Dr., Laboratory for Hydraulics, Hydrology and Glaciology (VAW), Swiss Federal Institute of Technology (ETH), 8092 Zürich
Labieuse, Vincent	Dr., MER, Rock Mechanics Laboratory, Swiss Federal Institute of Technology (EPFL), 1015 Lausanne
Margreth, Stefan	Swiss Federal Institute for Snow and Avalanche Research (SLF), Flüelastrasse 11, 7260 Davos Dorf
Minor, Hans-Erwin	Prof. Dr., Laboratory for Hydraulics, Hydrology and Glaciology (VAW), Swiss Federal Institute of Technology (ETH), 8092 Zürich
Montani-Stoffel, Sara	Dr., Rock Mechanics Laboratory, Swiss Federal Institute of Technology (EPFL), 1015 Lausanne
Studer, Jost A.	Dr., Studer Engineering, Thujastrasse 4, 8038 Zürich
Vischer, Daniel L.	Prof.em. Dr., c/o Laboratory for Hydraulics, Hydrology and Glaciology (VAW), Swiss Federal Institute of Technology (ETH), 8092 Zürich
Vulliet, Laurent	Prof. Dr., Soil Mechanics Laboratory, Swiss Federal Institute of Technology (EPFL), 1015 Lausanne
Zimmerli, Bruno	Dr., Fachhochschule FHZ, Hochschule für Technik und Architektur, Technikumstr. 21, 6048 Horw

## CONTENTS

	page
GENERAL REMARK AND SUMMARY	5
1. WIND LOADS	9
1.1 Introduction	9
1.2 Static and dynamic wind loads	9
1.3 Codes	10
1.4 Possibilities to prevent disasters	10
1.4.1 Roofs	10
1.4.2 Exterior walls and façades	11
1.4.3 Airdomes and tents	11
1.4.4 Scaffolding and cranes	13
1.4.5 Tanks, vessels and cooling towers	13
1.4.6 Towers, masts and stacks	13
1.4.7 Bridges	13
1.4.8 Erection stages	14
Reference	15
2. SNOW AVALANCHES	17
2.1 Introduction	17
2.2 Avalanche hazard and damage scenarios	18
2.3 Avalanche protection measures	19
2.3.1 General overview	19
2.3.2 Avalanche forecasting	19
2.3.3 Avalanche hazard mapping	22
2.3.4 Technical measures	23
2.3.5 Mountain forest	25
2.4 Avalanche risk and management	25
2.5 Research needs	25
2.5.1 Physics and mechanics of snow	25
2.5.2 Avalanche forecasting	25
2.5.3 Avalanche hazard mapping	26
2.5.4 Technical measures	26
2.5.5 Risk management	26
References	27
3. ICE AVALANCHES	29
3.1 Introduction	29
3.2 Historical ice avalanches	29
3.3 Starting zones and run-out distances of ice avalanches	31
3.4 Ice avalanche hazard mapping	33
3.5 Prediction of the break-off time	33
3.6 Outlook	35
References	35

4. ROCKFALLS	37
4.1 Introduction	37
4.2 Rockfall resilient infrastructure	38
4.2.1 Stabilisation methods	38
4.2.2 Protecting measures	38
4.3 Wire net rockfall barriers	39
4.3.1 Introduction	39
4.3.2 Full-scale testing of rockfall barriers	40
4.3.3 Forces and design criteria	41
4.3.4 Summary and outlook	42
4.4 Rock sheds	43
4.4.1 Introduction	43
4.4.2 Description of problem	43
4.4.3 Test device	43
4.4.4 Quantitative evaluation of forces	45
4.4.5 Inclined impacts	46
4.4.6 Conclusions	46
References	46
5. LANDSLIDES	49
5.1 Introduction	49
5.2 Main factors for landslide resilient infrastructure	49
5.3 Slide resilient infrastructure	50
5.3.1 Modification of slope geometry	50
5.3.2 Retaining structures	51
5.3.3 Internal slope reinforcement	51
5.3.4 Drainage	52
5.4 Debris flow resilient infrastructure	53
5.4.1 Escalated river protection scheme	53
5.4.2 Lateral protection dams and dikes	54
5.4.3 Emergency spillway structure	54
5.4.4 Structure separating bed load from water (Japanese trap)	54
5.5 Guidelines to improve the safety of disaster resilient infrastructure	54
References	55
6. IMPULSE WAVES	57
6.1 Introduction	57
6.2 Features of impulse waves	58
6.3 Impulse wave runup and overtopping	60
6.4 Consequences for infrastructure	61
6.4.1 Reservoir overtopping	61
6.4.2 Wave runup	61
6.5 Reservoir drawdown	62
6.6 Recommendations	63
Reference	63

<b>7. EARTHQUAKES</b>	<b>65</b>
7.1 Characteristics and damages	65
7.2 Importance of infrastructure for disaster response and rehabilitation	66
7.3 Vulnerability of infrastructure	66
7.3.1 Characteristics of infrastructural systems	67
7.3.2 Vulnerability of infrastructural systems	67
7.3.3 Vulnerability of infrastructural components	68
7.4 Risk mitigation measures	68
 <b>8. FOREST FIRES</b>	 <b>71</b>
8.1 Introduction	71
8.2 Forest fire data bases	71
8.3 Fire history	71
8.4 Effects of forest fires	72
8.5 Fire risk prediction	73
8.6 Fire behaviour modelling	73
8.7 Fire management	74
8.8 Conclusions	74
References	75
 <b>9. FLOOD PROTECTION AND INFRASTRUCTURAL DEFENSE</b>	 <b>77</b>
9.1 Dams and nuclear power plants	77
9.2 Pipeline-bound supply and disposal plants, transportation schemes	78
9.3 Buildings	81



## GENERAL REMARK AND SUMMARY

H.-E. Minor

Economic losses attributable to natural hazards rise steadily as the figures of Munich Reinsurance demonstrate. And each year a notable number of persons are killed or displaced at least for some time from their home areas. There are several reasons for the increase of impact by natural hazards:

- *Extension of settlements* including the corresponding infrastructure and productive plants is continuing. Not only the growing number of people is a reason but also the steady improvement of the built environment. Globalization and the pronounced division of labor in world economy will add even more in the future.
- There is and will be *more infrastructure* in the future that can be damaged; its construction cost is steadily increasing.
- Human activities with its settlements and infrastructure spread into endangered areas sometimes because no other space is available. This is convenient just on a short sight. *Construction costs* at flood plains for example are lower than on hilly ground. Since floods occur not every year, larger floods more than five years ago are normally forgotten.
- Sports-activities and *tourism* also push into more extreme areas and add to the necessary infrastructure.

All these structures are exposed to a high risk but at the same time they are expected to withstand disastrous impacts during natural hazards. This is not always possible. Man must realize that *100% safety does not exist*, especially not if structures are exposed consciously to natural hazard. They cannot be made safe against all possible impacts of natural hazards. In some cases it is simply not possible because of lack of technical means while it would be much too expensive in other situations.

Another approach is to define *hazard zones*. In the most critical zones with a high hazard potential construction could be prohibited, in the second zone with a moderate potential hazard, prescriptions should be made to armour structure against the natural hazard, and in a third zone owners have to be informed about existing hazard. Additionally it is essential to build up a *second line of defence* in case the first defense line fails. Needless to state that a warning system as well as rescue measures have to be installed. The warning system is then effective provided real-time-prediction is possible and the *rescue measures* are effective if extensive training has been carried out for specific hazards.

The various natural hazards have different character because they are governed by different physical processes. Accordingly, the methods of *hazard intervention* also differ. Table 0.1 attempts to demonstrate these differences and at the same time intends to show the possibilities of intervention. Three zones have been distinguished:

- Origin or source of hazard,
- Propagation or spreading area, and
- Zone of impact.

For extreme natural hazards, structures are essentially not able to resist, while other can be dealt with by a correct design. For many natural hazards it is nearly impossible to intervene at the source, for some, however, this approach is feasible such as landslides. Then, of course, this should be the first line of activity. As can be seen from Table 0.1 intervening in the propagation/spreading area is effective for many natural hazards.

In addition to the possible actions to be taken as listed in Table 0.1, consequent *regional planning* with definition of hazard zones would reduce considerably the impact of natural hazards to infrastructure. *Hazard zoning* should be defined not only for one natural hazard



scenario, but all natural hazards of a site should be investigated at the same time define the combined risk of endangered areas.

In this context it must be mentioned that different hazards are treated separately by the corresponding specialist. However, two or more natural hazards may *interact* and the experts have to come up with a common definition of solution. Future research has to take this aspect also into account.

The different chapters of this report aim to present the specific research needs in more detail or define the necessary activities to be carried out to make infrastructure more disaster resilient, as regarded by the authors.

Table 1 Possibilities of hazard intervention

Hazard Zone	① wind	② snow avalanches	③ ice avalanches	④ rockfall	⑤a landslides	⑤b debris flow	⑥ impulse waves	⑦ earthquake	⑧ forest fires	⑨ floods
Origin or source	none	supporting structures, artificial release of avalanches, silviculture, reforestation	none	limited	slope geometry, retaining structures, slope reinforce- ment, drainage. Large, steep slopes cannot be stabilized	check dams in torrents and scour measures, as for landslide	stabilize slides, draw down reservoir, control slide velocity	none		none
Propagation spreading area	little, consider vortex shedding	deviation dams, retaining dams, retarding structures	structures to divert avalanche away from vulnerable structures	various structures to hold back rockfall	none	protection dams to keep debris flow from vulnerable structures  Japanese trap	drawdown of reservoir	none		Retention basins, flood plain diversion structures, reduce sediment and drift wood supply
Zone of impact	apply state of the art design	shed structures	very limited	rock sheds	structures are essentially not able to resist thrust by lands- lide	see landslides	very limited	adequate design of structures, but also of infra- structure		increase river capacity, flood dykes, more space for river, increase erosion resistance

