

ANEXO 4 RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 97. Solicitaciones en columnas asociadas a tímpanos longitudinales. (Continuación).

10241			MIN					
				0.00	-1518.84	-19.85	-1581.18	-48.34
				3.30	-1506.96	-19.85	-1569.30	-48.34
10242	C	14	MAX					
				0.00	140.40	9.89	971.31	36.93
				3.30	152.28	9.89	983.19	36.93
10242			MIN					
				0.00	-1644.05	-16.49	-2474.95	-43.53
				3.30	-1632.17	-16.49	-2463.07	-43.53
Tercer Piso								
1032	A	2	MAX					
				0.00	-413.37	13.68	-529.50	21.18
				3.30	-401.49	13.68	-517.62	21.18
1032			MIN					
				0.00	-872.25	-0.84	-756.11	-8.35
				3.30	-860.37	-0.84	-744.23	-8.35
1033	A	3	MAX					
				0.00	-419.21	12.64	-495.81	23.47
				3.30	-407.33	12.64	-483.93	23.47
1033			MIN					
				0.00	-740.94	-0.26	-664.34	-11.09
				3.30	-729.06	-0.26	-652.46	-11.09
1034	A	4	MAX					
				0.00	-523.32	10.90	-532.65	19.67
				3.30	-511.44	10.90	-520.77	19.67
1034			MIN					
				0.00	-609.04	1.58	-599.71	-7.18
				3.30	-597.16	1.58	-587.83	-7.18
1035	A	5	MAX					
				0.00	-521.95	11.63	-541.31	23.24
				3.30	-510.07	11.63	-529.43	23.24
1035			MIN					
				0.00	-600.70	0.58	-581.34	-11.03
				3.30	-588.82	0.58	-569.46	-11.03
1036	A	6	MAX					
				0.00	-399.85	10.91	-490.26	19.91
				3.30	-387.97	10.91	-478.38	19.91
1036			MIN					
				0.00	-709.44	1.46	-619.04	-7.53
				3.30	-697.56	1.46	-607.16	-7.53
1037	A	7	MAX					
				0.00	-328.81	13.52	-448.92	24.01
				3.30	-316.93	13.52	-437.04	24.01
1037			MIN					
				0.00	-780.44	-1.44	-660.33	-11.92
				3.30	-768.56	-1.44	-648.45	-11.92

ANEXO 4. RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 97. Solicitaciones en columnas asociadas a tímpanos longitudinales. (Continuación).

10310	A	10	MAX					
				0.00	-548.65	12.18	-526.12	22.64
				3.30	-536.77	12.18	-514.24	22.64
10310			MIN					
				0.00	-621.81	0.16	-644.34	-10.30
				3.30	-609.93	0.16	-632.46	-10.30
10311	A	11	MAX					
				0.00	-476.22	11.69	-507.27	21.66
				3.30	-464.34	11.69	-495.39	21.66
10311			MIN					
				0.00	-708.78	0.78	-677.74	-9.18
				3.30	-696.90	0.78	-665.86	-9.18
10312	A	12	MAX					
				0.00	-510.08	12.73	-549.88	24.93
				3.30	-498.20	12.73	-538.00	24.93
10312			MIN					
				0.00	-684.58	-0.47	-644.78	-12.66
				3.30	-672.70	-0.47	-632.90	-12.66
10313	A	13	MAX					
				0.00	-408.79	11.70	-550.45	21.66
				3.30	-396.91	11.70	-538.57	21.66
10313			MIN					
				0.00	-900.53	0.79	-758.87	-9.17
				3.30	-888.65	0.79	-746.99	-9.17
10330	C	2	MAX					
				0.00	-254.25	-1.69	-158.02	6.59
				3.30	-242.37	-1.69	-146.14	6.59
10330			MIN					
				0.00	-1085.37	-10.00	-1181.61	-18.29
				3.30	-1073.49	-10.00	-1169.73	-18.29
10331	C	3	MAX					
				0.00	-451.74	-2.61	-257.01	3.02
				3.30	-439.86	-2.61	-245.13	3.02
10331			MIN					
				0.00	-896.58	-9.22	-1091.31	-14.85
				3.30	-884.70	-9.22	-1079.43	-14.85
10332	C	4	MAX					
				0.00	-612.69	-1.78	-446.64	6.85
				3.30	-600.81	-1.78	-434.76	6.85
10332			MIN					
				0.00	-816.28	-10.16	-982.34	-18.79
				3.30	-804.40	-10.16	-970.46	-18.79
10333	C	5	MAX					
				0.00	-558.54	-2.61	-295.80	3.71
				3.30	-546.66	-2.61	-283.92	3.71
10333			MIN					

ANEXO 4 RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 97. Solicitaciones en columnas asociadas a tímpanos longitudinales. (Continuación).

				0.00	-854.21	-9.16	-1116.95	-15.48
				3.30	-842.33	-9.16	-1105.07	-15.48
10334	C	6	MAX					
				0.00	-574.90	-0.49	-423.89	7.85
				3.30	-563.02	-0.49	-412.01	7.85
10334			MIN					
				0.00	-831.62	-11.54	-982.64	-19.87
				3.30	-819.74	-11.54	-970.76	-19.87
10335	C	7	MAX					
				0.00	-344.62	-1.36	-329.59	4.86
				3.30	-332.74	-1.36	-317.71	4.86
10335			MIN					
				0.00	-990.08	-10.48	-1005.11	-16.70
				3.30	-978.20	-10.48	-993.23	-16.70
10337	C	9	MAX					
				0.00	-604.40	-3.69	-645.56	-1.22
				3.30	-592.52	-3.69	-633.68	-1.22
10337			MIN					
				0.00	-791.87	-8.23	-750.71	-10.70
				3.30	-779.99	-8.23	-738.83	-10.70
10338	C	10	MAX					
				0.00	-305.87	-2.21	-112.95	5.87
				3.30	-293.99	-2.21	-101.07	5.87
10338			MIN					
				0.00	-1050.30	-9.92	-1243.22	-18.00
				3.30	-1038.42	-9.92	-1231.34	-18.00
10339	C	11	MAX					
				0.00	-441.20	-1.42	-390.79	7.60
				3.30	-429.32	-1.42	-378.91	7.60
10339			MIN					
				0.00	-886.91	-10.86	-937.32	-19.88
				3.30	-875.03	-10.86	-925.44	-19.88
10340	C	12	MAX					
				0.00	-479.84	-2.62	-208.00	4.15
				3.30	-467.96	-2.62	-196.12	4.15
10340			MIN					
				0.00	-828.01	-9.27	-1099.85	-16.04
				3.30	-816.13	-9.27	-1087.97	-16.04
10341	C	13	MAX					
				0.00	-361.66	-0.62	-209.37	8.23
				3.30	-349.78	-0.62	-197.49	8.23
10341			MIN					
				0.00	-947.01	-11.16	-1099.30	-20.00
				3.30	-935.13	-11.16	-1087.42	-20.00
Cuarto Piso								
1042	A	2	MAX					

ANEXO 4 RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 97. Solicitaciones en columnas asociadas a tímpanos longitudinales. (Continuación).

				0.00	-230.41	12.93	-221.09	17.46
				3.30	-218.53	12.93	-209.21	17.46
1042			MIN					
				0.00	-249.75	-0.19	-259.06	-4.72
				3.30	-237.87	-0.19	-247.18	-4.72
1043	A	3	MAX					
				0.00	-84.26	11.71	-112.61	20.41
				3.30	-72.38	11.71	-100.73	20.41
1043			MIN					
				0.00	-191.72	0.23	-163.38	-8.47
				3.30	-179.84	0.23	-151.50	-8.47
1044	A	4	MAX					
				0.00	-120.92	9.51	-126.88	15.85
				3.30	-109.04	9.51	-115.00	15.85
1044			MIN					
				0.00	-149.15	2.29	-143.19	-4.06
				3.30	-137.27	2.29	-131.31	-4.06
1045	A	5	MAX					
				0.00	-119.60	10.27	-127.27	19.90
				3.30	-107.72	10.27	-115.39	19.90
1045			MIN					
				0.00	-146.67	1.19	-139.01	-8.45
				3.30	-134.79	1.19	-127.13	-8.45
1046	A	6	MAX					
				0.00	-78.92	9.76	-110.07	16.03
				3.30	-67.04	9.76	-98.19	16.03
1046			MIN					
				0.00	-183.58	1.88	-152.43	-4.39
				3.30	-171.70	1.88	-140.55	-4.39
1047	A	7	MAX					
				0.00	-121.51	12.65	-118.27	20.24
				3.30	-109.63	12.65	-106.39	20.24
1047			MIN					
				0.00	-130.09	-1.02	-133.33	-8.61
				3.30	-118.21	-1.02	-121.45	-8.61
1048	A	8	MAX					
				0.00	-19.67	8.62	2.21	12.24
				3.30	-7.79	8.62	14.09	12.24
1048			MIN					
				0.00	-239.21	3.00	-261.09	-0.62
				3.30	-227.33	3.00	-249.21	-0.62
1049	A	9	MAX					
				0.00	-58.17	11.03	-28.45	21.92
				3.30	-46.29	11.03	-16.57	21.92
1049			MIN					
				0.00	-200.97	0.60	-230.69	-10.29

ANEXO 4. RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 97. Solicitaciones en columnas asociadas a tímpanos longitudinales. (Continuación).

				3.30	-189.09	0.60	-218.81	-10.29
10410	A	10	MAX					
				0.00	-10.44	10.46	-75.67	18.10
				3.30	1.44	10.46	-63.79	18.10
10410			MIN					
				0.00	-250.83	1.09	-185.60	-6.55
				3.30	-238.95	1.09	-173.72	-6.55
10411	A	11	MAX					
				0.00	26.75	9.69	-67.60	16.15
				3.30	38.63	9.69	-55.72	16.15
10411			MIN					
				0.00	-298.71	2.11	-204.36	-4.36
				3.30	-286.83	2.11	-192.48	-4.36
10412	A	12	MAX					
				0.00	25.69	11.07	-74.42	20.79
				3.30	37.57	11.07	-62.54	20.79
10412			MIN					
				0.00	-291.28	0.80	-191.16	-8.92
				3.30	-279.40	0.80	-179.28	-8.92
10413	A	13	MAX					
				0.00	-237.82	10.64	-232.65	16.67
				3.30	-225.94	10.64	-220.77	16.67
10413			MIN					
				0.00	-253.45	1.83	-258.62	-4.20
				3.30	-241.57	1.83	-246.74	-4.20
10429	C	1	MAX					
				0.00	-177.11	-1.44	-188.49	1.47
				3.30	-165.23	-1.44	-176.61	1.47
10429			MIN					
				0.00	-240.40	-5.41	-229.02	-8.33
				3.30	-228.52	-5.41	-217.14	-8.33
10430	C	2	MAX					
				0.00	-110.92	-3.13	-17.21	1.61
				3.30	-99.04	-3.13	-5.33	1.61
10430			MIN					
				0.00	-320.66	-8.71	-414.38	-13.45
				3.30	-308.78	-8.71	-402.50	-13.45
10431	C	3	MAX					
				0.00	-186.33	-4.59	-176.24	-2.82
				3.30	-174.45	-4.59	-164.36	-2.82
10431			MIN					
				0.00	-278.58	-7.21	-288.66	-8.98
				3.30	-266.70	-7.21	-276.78	-8.98
10432	C	4	MAX					
				0.00	-209.79	-3.44	-144.51	2.03
				3.30	-197.91	-3.44	-132.63	2.03

ANEXO 4. RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 97. Solicitaciones en columnas asociadas a tímpanos longitudinales. (Continuación).

10432			MIN					
				0.00	-284.59	-8.64	-349.86	-14.11
				3.30	-272.71	-8.64	-337.98	-14.11
10433	C	5	MAX					
				0.00	-218.09	-4.53	-192.21	-2.35
				3.30	-206.21	-4.53	-180.33	-2.35
10433			MIN					
				0.00	-268.55	-7.35	-294.43	-9.52
				3.30	-256.67	-7.35	-282.55	-9.52
10434	C	6	MAX					
				0.00	-197.56	-2.11	-135.64	2.86
				3.30	-185.68	-2.11	-123.76	2.86
10434			MIN					
				0.00	-287.77	-10.00	-349.69	-14.97
				3.30	-275.89	-10.00	-337.81	-14.97
10435	C	7	MAX					
				0.00	-169.03	-2.55	-175.81	-0.35
				3.30	-157.15	-2.55	-163.93	-0.35
10435			MIN					
				0.00	-322.69	-9.30	-315.92	-11.50
				3.30	-310.81	-9.30	-304.04	-11.50
10436	C	8	MAX					
				0.00	-153.58	-2.52	-197.67	1.66
				3.30	-141.70	-2.52	-185.79	1.66
10436			MIN					
				0.00	-341.48	-9.34	-297.40	-13.52
				3.30	-329.60	-9.34	-285.52	-13.52
10437	C	9	MAX					
				0.00	-163.02	-4.21	-143.33	-3.39
				3.30	-151.14	-4.21	-131.45	-3.39
10437			MIN					
				0.00	-325.26	-7.89	-344.95	-8.72
				3.30	-313.38	-7.89	-333.07	-8.72
10438	C	10	MAX					
				0.00	-111.34	-4.17	-5.45	-0.78
				3.30	-99.46	-4.17	6.43	-0.78
10438			MIN					
				0.00	-367.04	-7.87	-472.93	-11.27
				3.30	-355.16	-7.87	-461.05	-11.27
10439	C	11	MAX					
				0.00	-175.20	-3.31	-145.32	1.99
				3.30	-163.32	-3.31	-133.44	1.99
10439			MIN					
				0.00	-307.95	-8.95	-337.83	-14.24
				3.30	-296.07	-8.95	-325.95	-14.24
10440	C	12	MAX					

ANEXO 4. RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 97. Solicitaciones en columnas asociadas a tímpanos longitudinales. (Continuación).

				0.00	-194.64	-4.70	-161.25	-2.54
				3.30	-182.76	-4.70	-149.37	-2.54
10440			MIN					
				0.00	-281.96	-7.08	-315.35	-9.25
				3.30	-270.08	-7.08	-303.47	-9.25
10441	C	13	MAX					
				0.00	-121.68	-2.20	-13.74	2.35
				3.30	-109.80	-2.20	-1.86	2.35
10441			MIN					
				0.00	-306.10	-9.66	-414.05	-14.21
				3.30	-294.22	-9.66	-402.17	-14.21
10442	C	14	MAX					
				0.00	-140.32	-1.81	-134.37	-0.75
				3.30	-128.44	-1.81	-122.49	-0.75
10442			MIN					
				0.00	-278.82	-5.06	-284.77	-6.11
				3.30	-266.94	-5.06	-272.89	-6.11

Tabla 98. Solicitaciones en columnas asociadas a tímpanos transversales.

Elemento	Eje Transv	Eje Long.	Estado	Localización	Combinación 1		Combinación 2	
					Axial (kN)	Cortante (kN)	Axial (kN)	Cortante (kN)
					Combinación 1	Combinación 2	Combinación 1	Combinación 2
Segundo Piso								
1021	1	A	MAX					
				0	17.21	12.58	1237.51	30
				3.3	29.09	12.58	1249.39	30
1021			MIN					
				0	-1260.51	-5.87	-2480.81	-23.3
				3.3	-1248.63	-5.87	-2468.93	-23.3
1028	14	B	MAX					
				0	-501.81	16.3	68.98	39.21
				3.3	-489.93	16.3	80.86	39.21
1028			MIN					
				0	-1418.4	-4.29	-1989.19	-27.19
				3.3	-1406.52	-4.29	-1977.31	-27.19
10215	1	B	MAX					
				0	-573.14	12.35	-566.25	35.9
				3.3	-561.26	12.35	-554.37	35.9
10215			MIN					
				0	-772.34	-12.1	-779.23	-35.64
				3.3	-760.46	-12.1	-767.35	-35.64
10222	8	B	MAX					
				0	-911.83	14.91	-755.1	47.75
				3.3	-899.95	14.91	-743.22	47.75
10222			MIN					
				0	-1167.41	-14.69	-1324.14	-47.52
				3.3	-1155.53	-14.69	-1312.26	-47.52
10223	9	B	MAX					
				0	-477.92	15.73	610.59	49.7
				3.3	-466.04	15.73	622.47	49.7
10223			MIN					
				0	-1608.19	-15.67	-2696.7	-49.64
				3.3	-1596.31	-15.67	-2684.82	-49.64
10228	14	B	MAX					
				0	-322.63	19.36	115.75	57.64
				3.3	-310.75	19.36	127.63	57.64
10228			MIN					
				0	-1067	-19.25	-1505.38	-57.53
				3.3	-1055.12	-19.25	-1493.5	-57.53
10229	1	C	MAX					
				0	44.26	5.92	798.21	23.6
				3.3	56.14	5.92	810.09	23.6
10229			MIN					
				0	-1556.61	-12.27	-2310.57	-29.95
				3.3	-1544.73	-12.27	-2298.69	-29.95
10237	9	C	MAX					

Tabla 98. Solicitaciones en columnas asociadas a tímpanos transversales. (Continuación).

				0	-363.1	4.69	166.92	27.06
				3.3	-351.22	4.69	178.8	27.06
10237			MIN					
				0	-1808.75	-16.64	-2338.77	-39.01
				3.3	-1796.87	-16.64	-2326.89	-39.01
10242	14	C	MAX					
				0	140.4	9.89	971.31	36.93
				3.3	152.28	9.89	983.19	36.93
10242			MIN					
				0	-1644.05	-16.49	-2474.95	-43.53
				3.3	-1632.17	-16.49	-2463.07	-43.53
Tercer Piso								
1031	3	C	MAX					
				0	-166.67	6.55	254.01	12.35
				3.3	-154.79	6.55	265.89	12.35
1031			MIN					
				0	-603.85	1.30E-01	-1024.53	-5.68
				3.3	-591.97	1.30E-01	-1012.65	-5.68
10314	14	A	MAX					
				0	6.02	9.67	687.28	20.34
				3.3	17.9	9.67	699.16	20.34
10314			MIN					
				0	-771.97	-2.91	-1453.24	-13.58
				3.3	-760.09	-2.91	-1441.36	-13.58
10315	1	B	MAX					
				0	-349.86	4.54	-341.41	13.22
				3.3	-337.98	4.54	-329.53	13.22
10315			MIN					
				0	-482.65	-4.41	-491.1	-13.09
				3.3	-470.77	-4.41	-479.22	-13.09
10317	3	B	MAX					
				0	-445.01	6.14	-18.26	17.89
				3.3	-433.13	6.14	-6.38	17.89
10317			MIN					
				0	-869.06	-5.78	-1295.81	-17.53
				3.3	-857.18	-5.78	-1283.93	-17.53
10319	5	B	MAX					
				0	-423.6	6.07	24.69	18.36
				3.3	-411.72	6.07	36.57	18.36
10319			MIN					
				0	-893.74	-5.77	-1342.02	-18.07
				3.3	-881.86	-5.77	-1330.14	-18.07
10321	7	B	MAX					
				0	-486.68	6.08	-246.68	18.76
				3.3	-474.8	6.08	-234.8	18.76
10321			MIN					

ANEXO 4 RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 98. Solicitaciones en columnas asociadas a tímpanos transversales. (Continuación).

				0	-789.17	-5.93	-1029.17	-18.61
				3.3	-777.29	-5.93	-1017.29	-18.61
10322	8	B	MAX					
				0	-472.01	5.16	-160.38	16.53
				3.3	-460.13	5.16	-148.5	16.53
10322			MIN					
				0	-801.36	-5.03	-1113	-16.4
				3.3	-789.48	-5.03	-1101.12	-16.4
10323	9	B	MAX					
				0	-543.77	5.72	-397.56	17.67
				3.3	-531.89	5.72	-385.68	17.67
10323			MIN					
				0	-735.12	-5.57	-881.34	-17.52
				3.3	-723.24	-5.57	-869.46	-17.52
10326	12	B	MAX					
				0	-439.36	6.54	28.16	19.67
				3.3	-427.48	6.54	40.04	19.67
10326			MIN					
				0	-877.04	-6.29	-1344.56	-19.42
				3.3	-865.16	-6.29	-1332.68	-19.42
10328	14	B	MAX					
				0	-164.81	5.66	65.53	16.75
				3.3	-152.93	5.66	77.41	16.75
10328			MIN					
				0	-673.05	-5.53	-903.39	-16.62
				3.3	-661.17	-5.53	-891.51	-16.62
10329	1	C	MAX					
				0	-383.18	3.10E-01	-172.4	6.44
				3.3	-371.3	3.10E-01	-160.52	6.44
10329			MIN					
				0	-706.65	-6.82	-917.43	-12.96
				3.3	-694.77	-6.82	-905.55	-12.96
10331	3	C	MAX					
				0	-451.74	-2.61	-257.01	3.02
				3.3	-439.86	-2.61	-245.13	3.02
10331			MIN					
				0	-896.58	-9.22	-1091.31	-14.85
				3.3	-884.7	-9.22	-1079.43	-14.85
10333	5	C	MAX					
				0	-558.54	-2.61	-295.8	3.71
				3.3	-546.66	-2.61	-283.92	3.71
10333			MIN					
				0	-854.21	-9.16	-1116.95	-15.48
				3.3	-842.33	-9.16	-1105.07	-15.48
10335	7	C	MAX					
				0	-344.62	-1.36	-329.59	4.86

Tabla 98. Solicitaciones en columnas asociadas a tímpanos transversales. (Continuación).

				3.3	-332.74	-1 36	-317.71	4.86
10335			MIN					
				0	-990.08	-10.48	-1005.11	-16.7
				3.3	-978.2	-10 48	-993.23	-16.7
10336	8	C	MAX					
				0	-393.7	-7.54E-01	-143.52	8.44
				3.3	-381.82	-7.54E-01	-131.64	8.44
10336			MIN					
				0	-995.4	-10.98	-1245.58	-20.17
				3.3	-983.52	-10.98	-1233.7	-20.17
10337	9	C	MAX					
				0	-604.4	-3.69	-645.56	-1.22
				3.3	-592.52	-3.69	-633.68	-1.22
10337			MIN					
				0	-791.87	-8.23	-750.71	-10.7
				3.3	-779.99	-8.23	-738.83	-10.7
10340	12	C	MAX					
				0	-479.84	-2.62	-208	4.15
				3.3	-467.96	-2.62	-196.12	4.15
10340			MIN					
				0	-828.01	-9.27	-1099.85	-16.04
				3.3	-816.13	-9.27	-1087.97	-16.04
10342	14	C	MAX					
				0	-392.59	-3.24E-02	-286.24	4.15
				3.3	-380.71	-3.24E-02	-274.36	4.15
10342			MIN					
				0	-699.46	-6.52	-805.81	-10.7
				3.3	-687.58	-6.52	-793.93	-10.7
Cuarto Piso								
1041	13	C	MAX					
				0	-95.4	4.74	9.22	7.2
				3.3	-83.52	4.74	21.1	7.2
1041			MIN					
				0	-202.69	1.98	-307.31	-0.4754
				3.3	-190.81	1.98	-295.43	-0.4754
10414	14	A	MAX					
				0	-46.08	6.78	125.24	11.81
				3.3	-34.2	6.78	137.12	11.81
10414			MIN					
				0	-250.41	2.01E-03	-421.72	-5.03
				3.3	-238.53	2.01E-03	-409.84	-5.03
10415	1	B	MAX					
				0	-134.37	2.12	-130.52	6.55
				3.3	-122.49	2.12	-118.64	6.55
10415			MIN					
				0	-177.46	-2.19	-181.3	-6.62

ANEXO 4. RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 98. Solicitaciones en columnas asociadas a tímpanos transversales. (Continuación).

				3.3	-165.58	-2.19	-169.42	-6.62
10417	3	B	MAX					
				0	-212.67	4.26	-111.86	11.65
				3.3	-200.79	4.26	-99.98	11.65
10417			MIN					
				0	-312.16	-3.92	-412.97	-11.3
				3.3	-300.28	-3.92	-401.09	-11.3
10419	5	B	MAX					
				0	-205.14	3.97	-100.59	11.79
				3.3	-193.26	3.97	-88.71	11.79
10419			MIN					
				0	-321.28	-3.72	-425.84	-11.53
				3.3	-309.4	-3.72	-413.96	-11.53
10424	10	B	MAX					
				0	-197.07	4.02	-51.25	11.87
				3.3	-185.19	4.02	-39.37	11.87
10424			MIN					
				0	-334	-3.81	-479.81	-11.67
				3.3	-322.12	-3.81	-467.93	-11.67
10426	12	B	MAX					
				0	-214.03	4.02	-108.62	11.98
				3.3	-202.15	4.02	-96.74	11.98
10426			MIN					
				0	-310.58	-3.71	-415.99	-11.66
				3.3	-298.7	-3.71	-404.11	-11.66
10428	14	B	MAX					
				0	-80.13	2.57	-13.93	7.83
				3.3	-68.25	2.57	-2.05	7.83
10428			MIN					
				0	-233.32	-2.61	-299.53	-7.87
				3.3	-221.44	-2.61	-287.65	-7.87
10429	1	C	MAX					
				0	-177.11	-1.44	-188.49	1.47
				3.3	-165.23	-1.44	-176.61	1.47
10429			MIN					
				0	-240.4	-5.41	-229.02	-8.33
				3.3	-228.52	-5.41	-217.14	-8.33
10431	3	C	MAX					
				0	-186.33	-4.59	-176.24	-2.82
				3.3	-174.45	-4.59	-164.36	-2.82
10431			MIN					
				0	-278.58	-7.21	-288.66	-8.98
				3.3	-266.7	-7.21	-276.78	-8.98
10433	5	C	MAX					
				0	-218.09	-4.53	-192.21	-2.35
				3.3	-206.21	-4.53	-180.33	-2.35

ANEXO 4. RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 98. Solicitaciones en columnas asociadas a tímpanos transversales. (Continuación).

10433			MIN					
				0	-268.55	-7.35	-294.43	-9.52
				3.3	-256.67	-7.35	-282.55	-9.52
10438	10	C	MAX					
				0	-111.34	-4.17	-5.45	-0.7803
				3.3	-99.46	-4.17	6.43	-0.7803
10438			MIN					
				0	-367.04	-7.87	-472.93	-11.27
				3.3	-355.16	-7.87	-461.05	-11.27
10440	12	C	MAX					
				0	-194.64	-4.7	-161.25	-2.54
				3.3	-182.76	-4.7	-149.37	-2.54
10440			MIN					
				0	-281.96	-7.08	-315.35	-9.25
				3.3	-270.08	-7.08	-303.47	-9.25
10442	14	C	MAX					
				0	-140.32	-1.81	-134.37	-0.7527
				3.3	-128.44	-1.81	-122.49	-0.7527
10442			MIN					
				0	-278.82	-5.06	-284.77	-6.11
				3.3	-266.94	-5.06	-272.89	-6.11

ANEXO 4. RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 99. Solicitaciones en pedestales del primer nivel.

Elem.	Eje Long	Eje Transv	Estado	Localiz.	Combinación 1					Combinación 2				
					P	V2	V3	M2	M3	P	V2	V3	M2	M3
1011	A	1	MAX											
				0	61.43	206.61	605.44	1997.95	681.81	1930.44	572.35	198.8	656.06	1888.77
				3.3	97.07	206.61	605.44	0	0	1966.08	572.35	198.8	0	0
1011			MIN											
				0	-1892.69	-212.39	-600.12	-1980.39	-700.89	-3761.7	-578.14	-193.48	-638.49	-1907.85
				3.3	-1857.06	-212.39	-600.12	0	0	-3726.06	-578.14	-193.48	0	0
1012	A	2	MAX											
				0	-384.9	203.02	679.56	2242.54	669.96	-1036.87	578.13	221.26	730.16	1907.82
				3.3	-349.26	203.02	679.56	0	0	-1001.23	578.13	221.26	0	0
1012			MIN											
				0	-2884.73	-208.49	-678.82	-2240.11	-688	-2232.75	-583.59	-220.52	-727.72	-1925.86
				3.3	-2849.09	-208.49	-678.82	0	0	-2197.11	-583.59	-220.52	0	0
1013	A	3	MAX											
				0	-1332.51	199.34	679.91	2243.7	657.83	-1481.87	583.72	221.45	730.79	1926.29
				3.3	-1296.87	199.34	679.91	0	0	-1446.23	583.72	221.45	0	0
1013			MIN											
				0	-2070.36	-204.73	-679.7	-2243.01	-675.6	-1921	-589.11	-221.24	-730.11	-1944.06
				3.3	-2034.72	-204.73	-679.7	0	0	-1885.36	-589.11	-221.24	0	0
1014	A	4	MAX											
				0	-1582.28	194.91	680.93	2247.06	643.21	-1568.5	587.09	221.77	731.83	1937.38
				3.3	-1546.64	194.91	680.93	0	0	-1532.86	587.09	221.77	0	0
1014			MIN											
				0	-1788.86	-200.32	-680.92	-2247.02	-661.06	-1802.64	-592.5	-221.75	-731.79	-1955.24
				3.3	-1753.22	-200.32	-680.92	0	0	-1767	-592.5	-221.75	0	0
1015	B	5	MAX											
				0	-1523.63	836.08	366.16	741.36	2370.82	-1412.75	271.53	1099.3	2275.48	771.59
				3.3	-1487.99	836.08	366.16	389.1	387.86	-1377.11	271.53	1099.3	1274.15	124.21
1015			MIN											
				0	-1818.12	-835.84	-342.17	-740.67	-2370.48	-1929	-271.3	-1075.32	-2274.79	-771.25
				3.3	-1782.48	-835.84	-342.17	-467.57	-388.27	-1893.36	-271.3	-1075.32	-1352.63	-124.62
1016	B	6	MAX											
				0	-1303.1	188.46	682.1	2250.93	621.93	-1486.88	600.47	222.07	732.83	1981.56
				3.3	-1267.46	188.46	682.1	0	0	-1451.24	600.47	222.07	0	0
1016			MIN											
				0	-2012.46	-193.7	-682.26	-2251.45	-639.21	-1828.69	-605.71	-222.23	-733.36	-1998.84
				3.3	-1976.82	-193.7	-682.26	0	0	-1793.05	-605.71	-222.23	0	0
1017	B	7	MAX											
				0	-323.23	186.91	684.13	2257.64	616.8	-1052.16	610.51	223.02	735.97	2014.68
				3.3	-287.59	186.91	684.13	0	0	-1016.52	610.51	223.02	0	0
1017			MIN											
				0	-2753.83	-192.02	-684.35	-2258.35	-633.66	-2024.89	-615.62	-223.24	-736.68	-2031.53
				3.3	-2718.19	-192.02	-684.35	0	0	-1989.25	-615.62	-223.24	0	0

ANEXO 4. RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 99. Solicitaciones en pedestales del primer nivel. (Continuación).

1018	B	8	MAX											
				0	-615.84	187.44	685.22	2261.21	618.56	818.69	618.1	223.16	736.43	2039.73
				3.3	-580.2	187.44	685.22	0	0	854.33	618.1	223.16	0	0
1018			MIN											
				0	-2294.27	-192.54	-685.38	-2261.75	-635.37	-3728.8	-623.19	-223.32	-736.97	-2056.54
				3.3	-2258.63	-192.54	-685.38	0	0	-3693.16	-623.19	-223.32	0	0
1019	B	9	MAX											
				0	-1278.49	195.31	685.16	2261.02	644.51	-1156.94	631.38	222.86	735.45	2083.57
				3.3	-1242.85	195.31	685.16	0	0	-1121.3	631.38	222.86	0	0
1019			MIN											
				0	-1633.91	-200.33	-685.25	-2261.31	-661.08	-1755.46	-636.4	-222.95	-735.74	-2100.13
				3.3	-1598.27	-200.33	-685.25	0	0	-1719.82	-636.4	-222.95	0	0
10110	B	10	MAX											
				0	-950.02	203.91	684.71	2259.54	672.91	-1192.51	643.09	222.91	735.61	2122.19
				3.3	-914.38	203.91	684.71	0	0	-1156.87	643.09	222.91	0	0
10110			MIN											
				0	-2144.34	-208.75	-684.83	-2259.95	-688.87	-1901.86	-647.92	-223.03	-736.02	-2138.15
				3.3	-2108.7	-208.75	-684.83	0	0	-1866.22	-647.92	-223.03	0	0
10111	B	11	MAX											
				0	-1072.03	213.07	683.9	2256.86	703.14	-1342.75	655.76	222.66	734.76	2164.01
				3.3	-1036.39	213.07	683.9	0	0	-1307.11	655.76	222.66	0	0
10111			MIN											
				0	-2010.01	-217.8	-684.12	-2257.61	-718.74	-1739.29	-660.49	-222.88	-735.51	-2179.62
				3.3	-1974.37	-217.8	-684.12	0	0	-1703.65	-660.49	-222.88	0	0
10112	B	12	MAX											
				0	-1003.18	222.45	681.73	2249.72	734.08	-1218.07	669.16	221.96	732.45	2208.23
				3.3	-967.54	222.45	681.73	0	0	-1182.43	669.16	221.96	0	0
10112			MIN											
				0	-2119.31	-227.1	-682.09	-2250.91	-749.43	-1904.42	-673.81	-222.32	-733.64	-2223.58
				3.3	-2083.67	-227.1	-682.09	0	0	-1868.78	-673.81	-222.32	0	0
10113	B	13	MAX											
				0	-1416.82	231.87	679.3	2241.69	765.17	-1223.17	682.39	221.12	729.69	2251.89
				3.3	-1381.18	231.87	679.3	0	0	-1187.53	682.39	221.12	0	0
10113			MIN											
				0	-1742.3	-236.35	-680.1	-2244.33	-779.96	-1935.96	-686.87	-221.92	-732.33	-2266.68
				3.3	-1706.66	-236.35	-680.1	0	0	-1900.32	-686.87	-221.92	0	0
10114	B	14	MAX											
				0	39.68	241.79	600.17	1980.56	797.89	433.48	696.89	193.97	640.11	2299.73
				3.3	75.32	241.79	600.17	0	0	469.12	696.89	193.97	0	0
10114			MIN											
				0	-2097.4	-246.25	-605.56	-1998.34	-812.61	-2491.21	-701.35	-199.36	-657.89	-2314.44
				3.3	-2061.76	-246.25	-605.56	0	0	-2455.57	-701.35	-199.36	0	0
10115	B	1	MAX											
				0	-877.72	235.47	601.48	1984.9	777.07	-874.09	647.99	185.75	612.97	2138.36
				3.3	-842.08	235.47	601.48	0	0	-838.45	647.99	185.75	0	0

ANEXO 4 RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 99. Solicitaciones en pedestales del primer nivel. (Continuación).

10115			MIN											
				0	-1145.6	-236.97	-596.27	-1967.71	-781.99	-1149.23	-649.48	-180.54	-595.77	-2143.29
				3.3	-1109.96	-236.97	-596.27	0	0	-1113.59	-649.48	-180.54	0	0
10116	B	2	MAX											
				0	-1407.76	231.5	675.7	2229.83	763.96	-1396.32	654.73	206.79	682.42	2160.61
				3.3	-1372.12	231.5	675.7	0	0	-1360.68	654.73	206.79	0	0
10116			MIN											
				0	-1453.96	-232.66	-675.03	-2227.6	-767.78	-1465.39	-655.89	-206.12	-680.19	-2164.42
				3.3	-1418.32	-232.66	-675.03	0	0	-1429.75	-655.89	-206.12	0	0
10117	B	3	MAX											
				0	-1186.24	227.23	677.34	2235.24	749.86	-532.1	660.65	207.22	683.82	2180.15
				3.3	-1150.6	227.23	677.34	0	0	-496.46	660.65	207.22	0	0
10117			MIN											
				0	-1836.71	-228.33	-677.05	-2234.26	-753.5	-2490.85	-661.75	-206.92	-682.85	-2183.78
				3.3	-1801.07	-228.33	-677.05	0	0	-2455.21	-661.75	-206.92	0	0
10118	B	4	MAX											
				0	-1458.25	222.96	679.47	2242.26	735.76	-1444.91	666.67	207.81	685.78	2200.01
				3.3	-1422.61	222.96	679.47	0	0	-1409.27	666.67	207.81	0	0
10118			MIN											
				0	-1476.48	-224.04	-679.34	-2241.82	-739.33	-1489.82	-667.75	-207.68	-685.34	-2203.59
				3.3	-1440.84	-224.04	-679.34	0	0	-1454.18	-667.75	-207.68	0	0
10119	B	5	MAX											
				0	-1231.08	212.75	680.13	2244.42	702.09	-697.35	655.39	208	686.39	2162.77
				3.3	-1195.44	212.75	680.13	0	0	-661.71	655.39	208	0	0
10119			MIN											
				0	-1810.03	-214.82	-680.07	-2244.23	-708.9	-2343.77	-657.45	-207.94	-686.19	-2169.59
				3.3	-1774.39	-214.82	-680.07	0	0	-2308.12	-657.45	-207.94	0	0
10120	B	6	MAX											
				0	-1450.49	215.68	680.84	2246.77	711.75	-1441.81	681.85	208.19	687.04	2250.1
				3.3	-1414.85	215.68	680.84	0	0	-1406.17	681.85	208.19	0	0
10120			MIN											
				0	-1483.53	-216.52	-680.83	-2246.74	-714.52	-1492.21	-682.69	-208.18	-687.01	-2252.87
				3.3	-1447.89	-216.52	-680.83	0	0	-1456.57	-682.69	-208.18	0	0
10121	B	7	MAX											
				0	-1176.53	213.21	681.12	2247.7	703.58	-698.01	691.02	208.4	687.73	2280.37
				3.3	-1140.89	213.21	681.12	0	0	-662.37	691.02	208.4	0	0
10121			MIN											
				0	-1808.18	-213.92	-681.09	-2247.59	-705.94	-2286.71	-691.73	-208.37	-687.62	-2282.72
				3.3	-1772.54	-213.92	-681.09	0	0	-2251.07	-691.73	-208.37	0	0
10122	B	8	MAX											
				0	-1036.66	214.2	681.09	2247.6	706.87	-68.83	700.43	208.13	686.83	2311.41
				3.3	-1001.02	214.2	681.09	0	0	-33.19	700.43	208.13	0	0
10122			MIN											
				0	-2002.51	-214.87	-681.08	-2247.56	-709.08	-2970.33	-701.1	-208.12	-686.79	-2313.63
				3.3	-1966.87	-214.87	-681.08	0	0	-2934.69	-701.1	-208.12	0	0

ANEXO 4. RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 99. Solicitaciones en pedestales del primer nivel. (Continuación).

10123	B	9	MAX											
				0	-568.74	222.46	680.84	2246.78	734.12	1302.41	713.48	208.05	686.56	2354.48
				3.3	-533.1	222.46	680.84	0	0	1338.05	713.48	208.05	0	0
10123			MIN											
				0	-2486.31	-223.13	-680.88	-2246.89	-736.33	-4357.46	-714.15	-208.08	-686.68	-2356.69
				3.3	-2450.67	-223.13	-680.88	0	0	-4321.82	-714.15	-208.08	0	0
10124	B	10	MAX											
				0	-1354.52	232.52	680.49	2245.6	767.33	-1073.91	727.87	208.31	687.42	2401.98
				3.3	-1318.88	232.52	680.49	0	0	-1038.27	727.87	208.31	0	0
10124			MIN											
				0	-1633.82	-233.01	-680.58	-2245.9	-768.92	-1914.44	-728.35	-208.4	-687.72	-2403.57
				3.3	-1598.18	-233.01	-680.58	0	0	-1878.8	-728.35	-208.4	0	0
10125	B	11	MAX											
				0	-1458.51	242.91	679.42	2242.08	801.6	-1445.05	742.33	207.64	685.22	2449.7
				3.3	-1422.87	242.91	679.42	0	0	-1409.41	742.33	207.64	0	0
10125			MIN											
				0	-1476.56	-243.29	-679.54	-2242.47	-802.86	-1490.02	-742.71	-207.76	-685.61	-2450.96
				3.3	-1440.92	-243.29	-679.54	0	0	-1454.38	-742.71	-207.76	0	0
10126	B	12	MAX											
				0	-1169.12	253.37	677.1	2234.43	836.11	-442.48	757.07	206.93	682.86	2498.34
				3.3	-1133.48	253.37	677.1	0	0	-406.84	757.07	206.93	0	0
10126			MIN											
				0	-1856.23	-253.66	-677.39	-2235.39	-837.08	-2582.87	-757.37	-207.22	-683.83	-2499.31
				3.3	-1820.59	-253.66	-677.39	0	0	-2547.23	-757.37	-207.22	0	0
10127	B	13	MAX											
				0	-1413.28	264.11	675.01	2227.54	871.56	-1401.9	772.35	206.06	680.01	2548.76
				3.3	-1377.64	264.11	675.01	0	0	-1366.26	772.35	206.06	0	0
10127			MIN											
				0	-1447.64	-264.2	-675.7	-2229.8	-871.86	-1459.02	-772.44	-206.75	-682.27	-2549.06
				3.3	-1412	-264.2	-675.7	0	0	-1423.38	-772.44	-206.75	0	0
10128	B	14	MAX											
				0	-199.64	274.85	596.21	1967.48	907	1190.5	787.43	180.32	595.07	2598.52
				3.3	-164	274.85	596.21	0	0	1226.14	787.43	180.32	0	0
10128			MIN											
				0	-1778.81	-274.88	-601.43	-1984.71	-907.11	-3168.94	-787.46	-185.55	-612.3	-2598.63
				3.3	-1743.17	-274.88	-601.43	0	0	-3133.3	-787.46	-185.55	0	0
10129	C	1	MAX											
				0	284.23	211.14	607.15	2003.59	696.75	1476.71	576.9	205.06	676.7	1903.77
				3.3	319.87	211.14	607.15	0	0	1512.35	576.9	205.06	0	0
10129			MIN											
				0	-2703.95	-207.92	-601.89	-1986.24	-686.13	-3896.43	-573.68	-199.8	-659.34	-1893.14
				3.3	-2668.31	-207.92	-601.89	0	0	-3860.79	-573.68	-199.8	0	0
10130	C	2	MAX											
				0	-1164.54	207.4	682.43	2252.03	684.42	-874.78	582.41	228.81	755.08	1921.97
				3.3	-1128.9	207.4	682.43	0	0	-839.14	582.41	228.81	0	0

ANEXO 4 RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 99. Solicitaciones en pedestales del primer nivel. (Continuación).

10130			MIN											
				0	-1950.21	-204.01	-681.65	-2249.44	-673.22	-2239.97	-579.02	-228.03	-752.49	-1910.76
				3.3	-1914.57	-204.01	-681.65	0	0	-2204.33	-579.02	-228.03	0	0
10131	C	3	MAX											
				0	-862.41	203.5	684.3	2258.17	671.57	-677.42	587.32	229.48	757.28	1938.15
				3.3	-826.77	203.5	684.3	0	0	-641.78	587.32	229.48	0	0
10131			MIN											
				0	-2569.11	-200.07	-683.79	-2256.52	-660.23	-2754.11	-583.89	-228.98	-755.63	-1926.82
				3.3	-2533.47	-200.07	-683.79	0	0	-2718.47	-583.89	-228.98	0	0
10132	C	4	MAX											
				0	-1547.88	199.79	686.19	2264.44	659.29	-1238.75	592.9	230.02	759.06	1956.58
				3.3	-1512.24	199.79	686.19	0	0	-1203.11	592.9	230.02	0	0
10132			MIN											
				0	-2008.22	-196.37	-685.91	-2263.52	-648.01	-2317.34	-589.48	-229.74	-758.13	-1945.3
				3.3	-1972.58	-196.37	-685.91	0	0	-2281.7	-589.48	-229.74	0	0
10133	C	5	MAX											
				0	-1514.55	191.55	687.1	2267.43	632.1	-1123.25	585.17	230.28	759.91	1931.05
				3.3	-1478.91	191.55	687.1	0	0	-1087.61	585.17	230.28	0	0
10133			MIN											
				0	-2077.89	-188.82	-686.97	-2267.01	-623.1	-2469.19	-582.44	-230.15	-759.49	-1922.05
				3.3	-2042.25	-188.82	-686.97	0	0	-2433.55	-582.44	-230.15	0	0
10134	C	6	MAX											
				0	-945.32	193.34	687.64	2269.21	638.02	-1194.52	606.37	230.47	760.55	2001.02
				3.3	-909.68	193.34	687.64	0	0	-1158.88	606.37	230.47	0	0
10134			MIN											
				0	-2456.52	-189.68	-687.6	-2269.1	-625.95	-2207.33	-602.71	-230.43	-760.43	-1988.94
				3.3	-2420.88	-189.68	-687.6	0	0	-2171.69	-602.71	-230.43	0	0
10135	C	7	MAX											
				0	-1019.4	191.07	688.27	2271.3	630.54	-811.57	614.3	230.81	761.68	2027.18
				3.3	-983.76	191.07	688.27	0	0	-775.93	614.3	230.81	0	0
10135			MIN											
				0	-2195.46	-187.21	-688.2	-2271.05	-617.8	-2403.3	-610.44	-230.74	-761.43	-2014.44
				3.3	-2159.82	-187.21	-688.2	0	0	-2367.66	-610.44	-230.74	0	0
10136	C	8	MAX											
				0	-734.94	192.38	688.3	2271.38	634.87	-273.5	623.78	230.95	762.14	2058.47
				3.3	-699.3	192.38	688.3	0	0	-237.86	623.78	230.95	0	0
10136			MIN											
				0	-2507.73	-188.43	-688.09	-2270.71	-621.83	-2969.17	-619.83	-230.75	-761.46	-2045.43
				3.3	-2472.09	-188.43	-688.09	0	0	-2933.53	-619.83	-230.75	0	0
10137	C	9	MAX											
				0	-540.46	199.08	687.53	2268.84	656.96	741.74	633.52	230.4	760.32	2090.62
				3.3	-504.82	199.08	687.53	0	0	777.38	633.52	230.4	0	0
10137			MIN											
				0	-3044.98	-195.15	-687.37	-2268.33	-644	-4327.18	-629.59	-230.25	-759.81	-2077.66
				3.3	-3009.34	-195.15	-687.37	0	0	-4291.54	-629.59	-230.25	0	0
10138	C	10	MAX											

ANEXO 4 RESULTADO DEL ANALISIS DE LA VULNERABILIDAD ESTRUCTURAL

Tabla 99. Solicitaciones en pedestales del primer nivel. (Continuación).

			0	-1194.96	208.22	687.19	2267.72	687.12	-924.1	647.06	230.12	759.38	2135.3
			3.3	-1159.32	208.22	687.19	0	0	-888.46	647.06	230.12	0	0
10138			MIN										
			0	-2296.1	-204.18	-687.16	-2267.61	-673.79	-2566.95	-643.02	-230.08	-759.28	-2121.96
			3.3	-2260.46	-204.18	-687.16	0	0	-2531.31	-643.02	-230.08	0	0
10139	C	11	MAX										
			0	-1054.82	217.42	686.33	2264.9	717.5	-941.78	659.97	230.04	759.15	2177.91
			3.3	-1019.18	217.42	686.33	0	0	-906.14	659.97	230.04	0	0
10139			MIN										
			0	-2445.64	-213.31	-686.32	-2264.86	-703.92	-2558.68	-655.86	-230.03	-759.11	-2164.33
			3.3	-2410	-213.31	-686.32	0	0	-2523.04	-655.86	-230.03	0	0
10140	C	12	MAX										
			0	-1481.73	226.61	683.63	2255.99	747.82	-963.77	672.74	229.09	755.98	2220.05
			3.3	-1446.09	226.61	683.63	0	0	-928.13	672.74	229.09	0	0
10140			MIN										
			0	-2123.34	-222.41	-683.85	-2256.69	-733.96	-2641.3	-668.54	-229.3	-756.68	-2206.18
			3.3	-2087.7	-222.41	-683.85	0	0	-2605.66	-668.54	-229.3	0	0
10141	C	13	MAX										
			0	-982.24	236.22	681.72	2249.67	779.51	-698.08	686.6	228.59	754.34	2265.78
			3.3	-946.6	236.22	681.72	0	0	-662.44	686.6	228.59	0	0
10141			MIN										
			0	-2346.33	-231.87	-682.34	-2251.72	-765.17	-2630.49	-682.25	-229.21	-756.39	-2251.44
			3.3	-2310.69	-231.87	-682.34	0	0	-2594.85	-682.25	-229.21	0	0
10142	C	14	MAX										
			0	538.88	245.62	602.3	1987.59	810.54	1968.6	699.47	200.58	661.9	2308.26
			3.3	574.52	245.62	602.3	0	0	2004.24	699.47	200.58	0	0
10142			MIN										
			0	-2932.92	-241.17	-607.45	-2004.57	-795.85	-4362.65	-695.02	-205.72	-678.88	-2293.58
			3.3	-2897.28	-241.17	-607.45	0	0	-4327.01	-695.02	-205.72	0	0

Tabla 100. Solicitaciones máximas en pedestales.

Nudos	Combinación 1 Valores Máximos					Combinación 1 Valores Máximos				
	F1	F2	F3	M1	M2	F1	F2	F3	M1	M2
25015	416.62	175.21	2128.33	607.33	1677.78	143.52	462.70	4112.73	1677.24	542.82
25016	809.82	173.17	3015.63	595.26	1751.03	260.74	469.03	2548.08	1689.82	564.85
25017	747.66	171.01	2230.67	584.38	1711.87	242.93	474.33	2261.32	1705.16	553.19
25018	753.13	168.01	1957.35	575.58	1712.90	245.07	476.22	2156.05	1726.25	553.78
25019	681.25	184.97	1990.45	654.93	1708.18	222.41	542.88	2313.38	2001.93	552.24
25020	736.50	166.27	2179.60	558.06	1699.94	239.29	487.81	2181.82	1765.75	549.39
25021	711.92	168.25	2868.24	551.76	1680.13	233.56	497.66	2226.49	1784.93	543.64
25022	703.08	169.56	2460.53	558.86	1672.23	229.69	501.76	4094.40	1813.86	540.95
25023	698.89	176.16	1807.42	579.66	1669.72	227.14	518.04	2137.31	1847.59	539.90
25024	700.85	180.28	2313.89	604.21	1672.00	229.01	523.06	2278.55	1881.94	541.09
25025	711.75	186.30	2175.61	630.37	1680.58	232.64	532.22	2112.84	1918.88	543.96
25026	735.23	193.35	2293.45	657.55	1700.03	240.69	543.82	2294.65	1957.60	550.61
25027	804.96	199.78	1904.58	684.91	1748.60	264.24	552.78	2330.56	1996.94	567.24
25028	391.62	207.06	2524.78	712.45	1674.42	124.18	566.12	2948.72	2037.95	541.91
25029	411.33	330.12	1504.13	648.75	1666.71	143.67	906.71	1314.81	1789.77	516.99
25030	800.27	325.00	1553.69	636.18	1736.94	254.86	918.52	1569.50	1803.94	537.63
25031	731.55	319.39	1941.53	624.57	1690.89	235.33	926.71	2592.33	1820.27	524.77
25032	710.53	315.85	1582.58	615.37	1673.07	229.62	941.51	1594.91	1843.40	519.89
25033	698.77	382.45	1909.90	672.78	1664.33	226.39	1185.57	2427.27	2058.68	517.48
25034	695.70	308.14	1590.46	596.65	1660.81	225.49	963.62	1596.80	1885.61	516.48
25035	694.16	306.30	1913.59	589.74	1659.26	225.63	971.54	2387.43	1905.46	516.27
25036	694.17	310.45	2105.85	597.25	1659.18	225.19	985.23	3066.07	1936.10	516.07
25037	695.51	320.43	2588.49	619.16	1660.58	225.63	1003.36	4449.70	1971.30	516.54
25038	700.55	332.87	1740.81	645.60	1664.70	228.21	1023.34	2021.39	2008.78	518.20
25039	711.47	346.57	1582.32	673.58	1673.73	230.81	1043.39	1594.73	2048.31	520.85
25040	734.21	360.51	1960.94	702.48	1693.09	238.25	1063.79	2684.00	2089.38	527.25
25041	805.71	374.82	1555.44	731.75	1741.90	260.45	1084.73	1563.53	2131.53	542.83
25042	393.43	387.90	2127.61	760.78	1667.65	125.85	1103.21	3325.68	2174.24	518.06
25043	411.24	155.23	3114.53	609.45	1681.23	150.54	442.80	4300.28	1679.37	567.32
25044	805.35	153.24	2134.67	597.30	1752.22	274.52	448.62	2596.69	1691.81	590.00
25045	736.74	150.36	2727.21	586.37	1705.69	253.57	451.25	3100.65	1706.99	575.56
25046	713.51	149.81	2172.26	577.45	1687.02	246.09	460.98	2671.98	1727.80	569.66
25047	702.84	185.91	2246.21	607.67	1678.37	242.58	591.58	2831.55	1861.25	566.87
25048	698.47	147.65	2619.79	559.92	1674.44	241.16	472.57	2562.76	1767.33	565.55
25049	699.15	146.97	2361.67	553.74	1673.44	242.03	474.76	2767.39	1786.83	565.36
25050	699.41	151.04	2674.96	561.17	1673.55	242.95	486.68	3342.33	1816.53	565.65
25051	698.12	153.08	3210.96	581.41	1674.48	241.25	487.62	4696.39	1848.56	565.73
25052	704.23	159.87	2466.03	606.23	1678.98	242.72	501.18	2947.84	1883.80	567.18
25053	716.42	166.24	2616.85	632.41	1688.50	248.02	511.53	2944.18	1920.85	570.79
25054	737.36	172.43	2300.29	659.49	1707.57	254.94	520.26	3030.94	1959.26	577.26
25055	810.62	179.73	2503.16	686.94	1757.14	281.07	532.17	3021.79	1998.92	594.70
25056	394.99	184.33	3359.48	714.23	1682.38	134.43	537.85	4812.77	2039.15	567.93