

D.- RECOMMENDED ACTIONS AND COST

Just like it has been indicated in each case, the conclusions and recommendations given in Parts B and C of this report are supported by information collected at the site, essentially through visual inspection, and based on previous experiences. This, due to the fact that no access to structural plans, layouts nor calculation-data was possible, that would have allowed a more reliable quantitative evaluation.

Additionally, the Kingstown Hospital installations are subject to a Master Plan of reconstructions, relocations and expansions that extends itself to 11 phases, of which two have already been executed. Therefore, the recommended actions have the goal of mitigation and reduction of the present vulnerability to the natural threats.

All in all, in this Report a number of specific actions directed to reduce the vulnerability to natural threats are recommended; These are synthesized in Table D.1. Cost estimates and unitary prices are based in collected data from different sources; they may require local adjustments and are the following:

- Non-specialized labour	6 US\$/hour
- Specialized labour	15 US\$/hour
- Installed steel cost	0,8 US\$/Kg
- Forms and scaffolding cost	28 US\$/m ²
- Ready-mixed concrete	75 US\$/m ³
- Reinforced concrete slab of 11 cm in width + beams	65 US\$/m ²

TABLE D.1

SYNTHESIS OF THE RECOMMENDED ACTIONS TO REDUCE
THE FUNCTIONAL AND STRUCTURAL VULNERABILITY OF
THE KINGSTOWN HOSPITAL. ESTIMATED COST

BUILDING AND/OR INSTALLATION	RECOMMENDATION	ESTIMATED COST (US\$)
Buildings A and B	1. Verify the seismic resistance of the masonry walls incorporating the exsisting openings, specially in the long walls (North-South). If the resistance were not enough, tie-beams and/or confining tensors should be added; substitution of the slab with one made of reinforced concrete might be necessary.	3.000 15.000
	2. Placement of metallic strips to ensure proper union of the wooden columns to the wooden beams that support the corridor roofs.	3.000
	3. Fixing of the roof's gable-end in the Northern façade of Building A, near the Administration area.	8.000
	4. Correct the drainage deffect on top of the roof of the staircase complex of Buildings B-D, and repair the roof support beam in its deteriorated length.	3.000
	5. Place an adequate support, for example a metallic corbel, to supprot the aerial corridor that connects Buildings A and B-D.	2.000

TABLE D.1 (Cont.)

**SYNTHESIS OF THE RECOMMENDED ACTIONS TO REDUCE
THE FUNCTIONAL AND STRUCTURAL VULNERABILITY OF
THE KINGSTOWN HOSPITAL. ESTIMATED COST**

BUILDING AND/OR INSTALLATION	RECOMMENDATION	ESTIMATED COST (US\$)
Building C	1. Substitution of the wooden slabs by a reinforced concrete slab. 500 m ² x 65 US\$/m ² .	32.500
	2. Anchor to the walls, all equipments susceptible to tipping under the action of quakes and take the necessary measures to avoid the spill of reactivities.	2.000
Building D	1. Placement of metallic strips to secure the union of the reinforced concrete beams to the wooden planks over which the corridor roof rests.	3.000
	2. Repair the support beam (see point 4, Buildings A and B in this Table).	—
Buildings E and F	1. Check the origin of the humidity towards the Southern extreme of Building E, Radiology, and repair leak.	1.000

TABLE D.1 (Cont.)

**SYNTHESIS OF THE RECOMMENDED ACTIONS TO REDUCE
THE FUNCTIONAL AND STRUCTURAL VULNERABILITY OF
THE KINGSTOWN HOSPITAL. ESTIMATED COST**

BUILDING AND/OR INSTALLATION	RECOMMENDATION	ESTIMATED COST (US\$)
Buildings G and H	1. Verify the earthquake resistance, in the longitudinal direction (North - South) and the stability in perpendicular direction to its plane, of the masonry walls placed near the central axis, having the largest slenderness.	3.000
	2. Actions that come out from point 1, not able to be quantified for now.	
	3. Place a second row of fixation nails of the metallic sheeting, separated about 20 cm, towards the edges of the gable-ends, specially on the roofs with a slope of less than 30 degrees.	1.000
Building I	—	—
Building J	1. Eliminate the short-column effect at the ends of the Eastern and Northern façades, filling the holes that generate short columns with reinforced elements.	5.000
Water supply	1. The water reserve in the present hospital's elevated tanks (25.900 liters) covers 24 hours demand; it is recommended to expand this reserve to 72 hours, with a subterranean tank of twice the capacity.	12.000

TABLE D.1 (Cont.)

**SYNTHESIS OF THE RECOMMENDED ACTIONS TO REDUCE
THE FUNCTIONAL AND STRUCTURAL VULNERABILITY OF
THE KINGSTOWN HOSPITAL. ESTIMATED COST**

BUILDING AND/OR INSTALLATION	RECOMMENDATION	ESTIMATED COST (US\$)
Energy	1. Anchor the high voltage generator located next to the emergency plant.	1.000
	2. Anchor the gasoil tank that supplies the emergency plant to the support walls.	1.000
Gas storage cylinders	1. Establish simple fixation systems for the metallic bottles or gas cylinders to the walls.	1.000
Cremation Plant	1. Anchor the gasoil tank that supplies the cremation plant to the support walls.	1.000
Gable-end and roof-ridge edges	1. Just like in the recommendation for Buildings G and H, a second row of fixation nails should be placed towards the edges of the roof-ridge, specially in roofs with slopes less than 30 degrees. This is a general recommendation, since not all the roof coverings could be inspected.	3.000

According to the information supplied by the Hospital's Administration, the Emergency Plan elaborated for contingency situations is practiced. Nonetheless, the internal communications system that now depends of the telephonic installation is planned to be updated in the next phase of the Master Plan mentioned before.

Finally, it is recommended that the Hospital's Administration recovers all the structural, architectural and installations drafts and layouts, and creates an ad-hoc file for their internal consultation. The convenience of this measure was shared by the Maintenance Chief, Mr Henderson.

REFERENCES

- AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI) (1982). Minimum Design Loads for Buildings and other Structures ANSI A58.1-1982, New York.
- APPLIED TECHNOLOGY COUNCIL (ATC) (1978). Tentative Provisions for the Development of Seismic Regulations for Buildings. Report ATC-3, San Francisco, California.
- ASOCIACION COLOMBIANA DE INGENIERIA SISMICA (AIS) (1984). Código Colombiano de Construcciones Sismo-resistentes, Santafé de Bogotá.
- ASPINALL W. P., SHEPHERD J., WOO G., WIGHTMAN A., ROWLEY K., LYNCH L. and AMBEH W. (1994). Seismic Ground Motion Hazard Assessment at a Site near a Segmented Subduction Zone: the Roseau Dam, Saint Lucia, West Indies. Earthquake Spectra, 10:2, 259-292.
- BERZ, G. (1994). The worldwide increasing windstorm risk: Damage analysis and perspectives for the future. In: Structural Safety and Reliability, vol 3, ed. by Schuëller, Shinozuka & Yao. Balkema, Rotterdam.
- BROWNE, C. Comunicación personal, Kinstown, Julio 1996.

CARIBBEAN UNIFORM BUILDING CODE (CUBIC) (1985). Part 2. Section 3. Structural Design Requirements. Earthquake Load. Georgetown, Guyana.

CARIBBEAN UNIFORM BUILDING CODE (CUBIC) (1986).Part 2.Section 2. Structural Design Requirements. Wind Load. Georgetown, Guyana.

COMISION VENEZOLANA DE NORMAS TECNICAS (COVENIN-MINDUR) (1986). Acciones del Viento sobre las Construcciones. Norma COVENIN 2003-86. Caracas.

COMISION VENEZOLANA DE NORMAS TECNICAS (COVENIN-MINDUR) (1988). Criterios y Acciones Minimas para el Proyecto de Edificaciones. Norma COVENIN 2002-88, Caracas.

DOREL, J. (1981). *Seismicity Gap in the Lesser Antilles arc and Earthquake Hazard in Guadeloupe.* Geophys. J. Royal Astronomical Society, 67 679-695.

FLORIS, C., COLOMBO, A., MAZZUCHELLI, A. and MORELLO, M. (1990). *Analisi Statistica dei Dati Eolici in Milano Centro.* I Convegno Nazionale di Ingegneria del Vento, Ottobre, Firenze.

GIBBS, T. *Comunicación personal*, Julio 1996.

GIESECKE, A. *Comunicación personal*, Agosto 1996.

GRASES, J. (1971). The Seismicity of the Caribbean Region. Imperial College, London.

GRASES, J. (1990). Terremotos Destruidores del Caribe. UNESCO-RELACIS, Montevideo.

GRASES, J. (1996). *Estrategia Ingenieril de Mitigación de las Amenazas Naturales*. A ser presentado en: IDNDR CARIBBEAN ROVING SEMINAR (ICAROS) 96.

INSTITUTO PANAMERICANO DE GEOGRAFIA E HISTORIA (1996). *Mapa regional de Isoaceleraciones del Caribe Oriental*, coordinado por J. Shepherd para el IPGH (versión preliminar gentilmente cedida por el Dr. T. GIBBS).

LANDSEA, C.W. (1993). *A climatology of intense (or major) Atlantic Hurricanes*. Monthly Weather Review, 121, 1703-1713.

MÜNCHENER RE (1988) Mapa Mundial de los Peligros de la Naturaleza. München.

ORGANIZACION DE ESTADOS AMERICANOS (1993). Manual sobre el Manejo de Peligros Naturales en la Planificación para el Desarrollo Regional Integrado. Departamento de Desarrollo Regional y Medio Ambiente, OEA, Washington.

PROYECTO ANDINO DE DESARROLLO TECNOLÓGICO, RECURSOS FORESTALES TROPICALES (PADT-REFORT) (1987). Manual de Diseño para Maderas del Grupo Andino. Junta del Acuerdo de Cartagena, Lima /edición de fecha dudosa/.

ROBSON, G.R. (1964). *An Earthquake Catalogue for the Eastern Caribbean 1530-1960*. Bulletin of the Seismological Society of America, 54, 785-832.

SAFFIR, H.S. (1989). *Florida's approach to hurricane-resistant design and construction*. Journal of Wind Eng and Ind Aerodynamics, 32, 221-230.

SHEPHERD J. and LYNCH L. (1992) An earthquake catalogue for the Caribbean. Part I. the pre-instrumental period 1502-1900. Lancaster, 1992.

SIMKIN T., et al (1981). Volcanoes of the World. Pennsylvania, USA.

UNIFORM BUILDING CODE (UBC) (1994), Whittier, California.